












**Accessories / Assembly kits for leak detector type D29:**

Artikelnr. Part.No.	Description	Material	
49300090	<b>Dry beads 250 ccm</b>		
49300086	<b>Dry beads 1 ltr.</b>		
49300087	<b>Dry beads 2 ltr.</b>		
49300088	<b>Dry beads 10 ltr.</b>		
42001161	<b>Assembly kit for leak detector type D29,</b> connected to: <b>- double walled pipes</b> Consist of: - 2 pcs connectors (pressure and measuring line) - 1 pc test valve unit - connectors: pipe <b>1/4 inch,</b> outside tubing diameter <b>6 mm</b>	Brass	
42001160	<b>Assembly kit for leak detector type D25,</b> <b>D26, D29</b> connected to: <b>- double walled pipes</b> Consist of: - 1 pc pressure connector - 1 pc test valve unit - connectors: pipe <b>1/4 inch,</b> - for D29: connect pressure line with measuring line via separate t-connector outside tubing diameter <b>6 mm</b> - material: <b>brass</b>	Brass	
42001060	<b>Assembly kit for leak detector type D25,</b> <b>D26, D29</b> , connected to: <b>- double walled pipes</b> Consist of: - 1 pc pressure connector - 1 pc test valve unit - connectors: pipe <b>1 inch,</b> - for D29: connect pressure line with measuring line via separate t-connector outside tubing diameter <b>6 mm</b> - material: <b>brass</b>	Brass	
42003578	<b>Air dryer (external)</b> for leakdetector type D9, D29, <b>180ccm,</b> with mounting angle, connectors for 4mm (inside hoseØ), <b>without dry beads</b>	Plastics	<p>Best.Nr. 42003578 180 cm<sup>3</sup>, LTR 3</p> 

**Accessories / Assembly kits for leak detectot type D29:**

Artikelnr. Part.No.	Description	Material	
42003589	<b>Air dryer</b> (external) for leakdetector type D9, D29, <b>350ccm</b> , with mounting angle, connectors for 4mm (inside hoseØ), <b>without dry beads</b>	Plastics	 <p>Best. Nr. 42003589 34,6 cm³ - LTR 4</p>
42003591	<b>Air dryer</b> (external) for leakdetector type D9, D29, <b>550ccm</b> , with mounting angle, connectors for 4mm (inside hoseØ), <b>without dry beads</b>	Plastics	 <p>Best. Nr. 42003591 50,0 cm³ - LTR 4</p>
42001982	<b>Manifold kit</b> for leak detector type <b>D29</b> , connected to: <b>- 2 double walled pipes</b> Consists of: - 2 pcs. ball valves - 2 pcs. manometer 6 bar - Connectors for <b>6 mm</b> outside tubing diameter	Brass	
42001983	<b>Manifold kit</b> for leak detector type <b>D29</b> , connected to: <b>- 3 double walled pipes</b> Consists of: - 3 pcs. ball valves - 3 pcs. manometer 6 bar - Connectors for <b>6 mm</b> outside tubing diameter	Brass	
42001984	<b>Manifold kit</b> for leak detector type <b>D29</b> , connected to: <b>- 4 double walled pipes</b> Consists of: - 4 pcs. ball valves - 4 pcs. manometer 6 bar - Connectors for <b>6 mm</b> outside tubing diameter	Brass	
42001985	<b>Manifold kit</b> for leak detector type <b>D29</b> , connected to: <b>- 5 double walled pipes</b> Consists of: - 5 pcs. ball valves - 5 pcs. manometer 6 bar - Connectors for <b>6 mm</b> outside tubing diameter	Brass	
42001986	<b>Manifold kit</b> for leak detector type <b>D29</b> , connected to: <b>- 6 double walled pipes</b> Consists of: - 6 pcs. ball valves - 6 pcs. manometer 6 bar - Connectors for <b>6 mm</b> outside tubing diameter	Brass	